



Designed and manufactured in the UK... top quality equipment that works!



www.dialadigger.co.uk







GROUND DRIVEN SALT SPREADER GDS150R - is the smallest in the GDS range and is designed for use with any type of road salt including wet rock salt, used behind an ATV, UTV or similar vehicle. It has a stainless steel hopper and will spread from 1.5 to 12.0 metres depending on forward speed. Seen here in use with an ATV and SNOW PLOUGH S228.



GROUND DRIVEN SALT SPREADER GDS250R - seen here with an optional Flashing Beacon GDS106.



footpaths. etc.





GROUND DRIVEN SALT SPREADERS GDS200R / 250R - featuring a choice of standard gearbox for spread widths of 1.5 - 10.0 metres or high speed gearbox for 3.0 - 14.0 metres, at speeds between 5-15 mpt





ENGINE DRIVEN SALT SPREADER PDS354D - can be secured in a pick-up or onto a trailer to provide a versatile spreading unit. Trailed model also available.







POWER BRUSH UTS215BR - for front use on UTVs has a 1.68m

width and remote electric controls to angle and lift the brush.

Finance packages available on these products: please see our website for more details

Visit Logic online www.LogicToday.co.uk for:

- Detailed specifications
- Product videos
 News & Events



/ideos Available Online Indicates video of product in action, visit: LogicToday.co.uk

Our national dealer network gives you:

- Local delivery Pre-delivery inspection
- Instruction on delivery
 Support and after sales service

Dial a Digger

0800-0-853-853

www.dialadigger.co.uk

Logic builds high standards of safety and reliability into its products. For example all towed products benefit from a swivel hitch built into the drawbar. Where fitted, low ground pressure wheels and tyres all have bead-lock rims.

These essential features are included without compromise to improve customer safety. Always ensure the vehicle you intend to use with Logic products is suitable for the task. Due to continuous development Logic Manufacturing Ltd. reserves the right to alter specifications without notice.